

# Comments on "Anomalous Hydrodynamic Drafting of Interacting Flapping Flags"

Guanghua Zhu

Qinghaihu Centre, 2, Street Hua-Yuan South, Xining 810000, China

## Abstract

We make remarks on Ristroph and Zhang's [*Phys. Rev. Lett.* **101**, 194502 (2008)] paper. We argue especially that due to the interferences the calibration procedures in [1] were not complete and this will induce some measurements' error.

Ristroph and Zhang just presented an interesting observation about the inverted drag relationship for 6 tandem flags where inverted drafting directly suggests hydrodynamic repulsion between flags [1]. Unfortunately they only presented their observations about the inverted drag relationship for 2 and 6 tandem flags [1]. They didn't illustrate the crucial results : 3 tandem flapping flags in [1]. There are inconsistencies as evidenced from Fig. 2 and Fig. 4 (b), (c). In Fig. 2,  $D/D_0 \sim 0.5, 1$  for the first flag while  $D/D_0 \sim 1, 1.5$  for the 2nd. one considering the spacing  $G/L = 0, 0.6$ , respectively? In Fig. 4 (b), (c);  $D/D_0 \sim 0.5, 0.8$  for the first flag while  $D/D_0 \sim 0.7, 1.3$  for the 2nd. one considering the spacing  $G/L = 0, 0.6$ , respectively? Is the difference due to interferences and upstream influences?

To experimentally capture the forcing as well as model the interaction of shapechanging bodies, they inserted thin flexible filaments into a flowing soap film [2]. Each filament is fixed at its upstream end to a thin wire, a flagpole that extends out of the film, while the rest of the thread hangs free in the film. It means the conventional sting (a *smart* support for force and moment measurements) in wind and/or water tunnel has been moved from the downstream part of a test section to the upstream part [3]. Although the diameter ( $34\mu\text{m}$ ? [2]) of the flagpole (or a sting) is small once it is inserted transverse to the flow (in fact, a soap solution with air interfaces along upper and lower fluctuating surfaces; film thickness :  $4.7\mu\text{m}$  [1]) there will be wakes generated and small vortices shedding. The later complex flow structure will influence the downstream flow condition of one flexible flag (a thread with diameter :  $300\mu\text{m}$  [1]) or tandem flags behind. To be precise, the upstream flow is not essentially a uniform flow or free of turbulence.

To obtain the detailed drag-force characteristics it is important to calibrate necessary sets of data beforehand. As mentioned in [1], Ristroph and Zhang *only* measured the time-averaged streamwise fluid force :  $D_0$  or the drag on an *isolated* flag [2] which is served as a normalization or a baseline [1] for comparison. The present author argues that above procedure is not enough

for drawing a conclusion about the six tandem flags.

Normally the force or moment measurements conducted in wind or water tunnels are for one-body or one-object (say, scaled airfoil or aircraft model) [3]. Considering the multi-body purpose (configuration) as well as the unsteady flow characteristics the interferences and active or passive influences between different bodies (located either forward or backward with respect to (w.r.t.) a referenced body (say,  $D_0$  in [1])) which are confined in a limited test section should be carefully examined firstly. It means, e.g., for 2 flags, the same measuring procedure should be conducted for both configurations to eliminate the possible noises : (a) to put flag 1 forward with flag 2 rearward, and (b) to put flag 2 forward with flag 1 rearward. The measured drags are :  $D_{1f}^f$ ,  $D_{1r}^r$ ,  $D_{1f}^r$ , and  $D_{1r}^f$ , respectively.

To be specific, we can check whether  $D_{1f}^f = D_{1f}^r$  or  $D_{1r}^r = D_{1r}^f$ ? For each flag of this case, Ristroph and Zhang thought that  $D_0$  is the same for either the forward one or the rearward one. However, as mentioned above, once there is a sting (flagpole) or a flag mounted inside the flow, there are severe flow (or structure) induced fluctuations (considering the force or moment induced) generated. The second flag, no matter it will be located forward or rearward to the already mounted one with a spacing in-between, once being inserted into the flow, the final situation is different from that two tandem flags being mounted simultaneously into the flow! The present author proposes that we should compare the above 4 drag forces for each flag with  $D_0$ . We believe that the normalization or baseline drag force for two tandem flags should be selected from either  $D_{1f}$  or  $D_{1r}$ . The subsequent results considering the same demonstrating procedure of Fig. 2 in [1] should be different as the normalization drag is different from  $D_0$ . With this process, we can minimize the interferences and mutual influences for multi-body configurations. Similar procedures must be conducted for  $i \geq 3$  (w.r.t.  $D_i$ ), e.g.,  $i = 5$  to check the validness of 6 tandem flags or Fig. 4 (b), (c) in [1].

To conclude in brief, we believe the effects of interferences and mutual influences could tune the conclusion made in [1]. The preliminary direct check is presented above and the other check is to put the next or following flag upstreamwise instead downstreamwise when one flag has been inserted into the soap solution.

## References

- [1] L. Ristroph and J. Zhang, Phys. Rev. Lett. **101**, 194502 (2008).
- [2] S. Alben, M. Shelley, and J. Zhang, Nature **420**, 479 (2002). S. Alben, M. Shelley, and J. Zhang, Phys. Fluids **16**, 1694 (2004).
- [3] E.C. Yates, Jr. AGARD standard aeroelastic configuration for dynamic response. Candidate Configuration I-Wing 445.6, NASA TM 100492 (1987).